

SPECIFICATIONS

Current Rating: 3 AMP

Contact Resistance: 10mΩ Max.

Dielectric Voltage: 1000V AC for one minute

Operating Temperature: -40°C ~ +105°C

MATERIAL

Insulator: PPS+30%G.F. , UL94V-0

Contact Pin: Copper Alloy

ORDER INFORMATION

5 M H 2 M 2 8 N - 2 X X X X B T U - 0 0 0 0 - 0 1

2: Dual Rows

No. of Contacts
(02-40)

G0:Gold Flash

GB:10u"

GF:15u"





GD:30u"

T0:Tin Plated

B:Black

T:Tube

RoHS



Recommended PCB Layout
(PCB TOLERANCE ±0.1)

REV.	ECN NO. OR DESCRIPTION	REVISED	DATE

 糧德精密有限公司 Amtek Technology Co., Ltd. TEL: 886-2-2260-6878 FAX: 886-2-2260-8030	品名 TITLE	Machine Pin Header 2.0mm				頁數 Page	1/1
	品號 PART NO.	5MH2M28N-2XXXXBTU-0000-01				繪圖 DRAWN	Gary 2017/11/03
	圖號 DRAWING NO.	GN003-GA727		版本 REV.	A	核對 CHECKED	Jason 2017/11/03
	客戶品號 CUSTOMER P/N			比例 SCALE	None	承認 APPROVED	Jason 2017/11/03
	公差 TOLERANCE	.X ± 0.40 .XX ± 0.25		X° ± 3°	單位 UNIT	mm	THIRD ANGLE PROJECTION 