

SPECIFICATIONS

Current Rating: 1 AMP
Contact Resistance: 10mΩ Max.
Dielectric Voltage: 1000V AC for one minute
Operation Temperature: -40°C to +105°C


MATERIAL

Insulator: PPS+30%G.F, UL94V-0
Contact Pin: Copper Alloy



ORDER INFORMATION

5MH3S19N-3XXXBXU-0810-01

3:Triple Row	No. of Contacts Per Row(02~50)	G0:Gold Flash GB:Au 10u" GF:Au 15u" GD:Au 30u"	B:Black Insulator	T:Tube X:Box	RoHS
--------------	-----------------------------------	---	-------------------	-----------------	------



Recommended PCB Layout
(PCB TOLERANCE ±0.1)



 Amtek Technology Co., Ltd. TEL: 886-2-2260-6878 FAX: 886-2-2260-8030				品名 TITLE MACHINE PIN HEADER 1.27mm				頁數 Page	1/1
				品號 PART NO. 5MH3S19N-3XXXXBXU-0810-01				繪圖 DRAWN	Roy 2017/11/02
				圖號 DRAWING NO. GN003-RR091				核對 CHECKED	Jason 2017/11/02
				客戶品號 CUSTOMER P/N				承認 APPROVED	Jason 2017/11/02
				公差 TOLERANCE .X ±0.40 .XX ±0.25 X°±3°				單位 UNIT mm	THIRD ANGLE PROJECTION 
REV.	ECN NO. OR DESCRIPTION			REVISED	DATE				