

SPECIFICATIONS

Current Rating: 3 AMP

Contact Resistance: 10mΩ Max.

Dielectric Voltage: 1000V AC for one minute

Operating Temperature: -40°C ~ +105°C

MATERIAL




Insulator: PPS+30%G.F. , UL94V-0

Contact Pin: Copper Alloy


ORDER INFORMATION

5 M S 1 R 3 0 N - 2 X X X X B X U - 0 0 0 0 - 0 1

2: Dual Rows	No. of Contacts (02-50)	S0:Gold Flash SB:10u" SF:15u" SD:30u" T0:Tin Plated	B:Black	T:Tube X:Box	RoHS
--------------	----------------------------	---	---------	-----------------	------



Recommended PCB Layout
(PCB TOLERANCE ±0.1)



REV.	ECN NO. OR DESCRIPTION	REVISED	DATE

 糧德精密有限公司 Amtek Technology Co., Ltd. TEL: 886-2-2260-6878 FAX: 886-2-2260-8030	品名 TITLE	MACHINE PIN HEADER 2.54mm				頁數 Page	1/1
	品號 PART NO.	5MS1R30N-2XXXXBXU-0000-01				繪圖 DRAWN	Gary 2017/11/13
	圖號 DRAWING NO.	GN003-GA761	版本 REV.	A	核對 CHECKED	Jason 2017/11/13	
	客戶品號 CUSTOMER P/N		比例 SCALE	None	承認 APPROVED	Jason 2017/11/13	
	公差 TOLERANCE	.X ± 0.40 .XX ± 0.25	單位 UNIT	mm	THIRD ANGLE PROJECTION		