

MATERIAL

Insulator: Nylon 9T, UL94V-0, Black
Contact Pin: brass

ORDER INFORMATION

5PH1DMA25-1XX-XXNXXU-A1B-00

1:Single Row

No. of contacts
Per Row(02~40)

G0:Gold Flash
GA:Au 5u"
GB:Au 10u"
GC:Au 20u"
GD:Au 30u"
T0:Tin Plated

S0:Selective Au
SA:Selective Au 5u"
SB:Selective Au 10u"
SC:Selective Au 20u"
SD:Selective Au 30u"
TE:Tin 200u"

A:A Type
(Odd & Even Pin)
B:B Type
(Only Even Pin)

N:W/O Peg

R:T/R With Cap
H:T/R W/O Cap
C:Tube With Cap (5 Pin ↑)
T:Tube W/O Cap (5 Pin ↑)
X:Box

U:RoHS+Hi-Temp.

EX:060XXX049
A:6.0
L1:As Required
B:4.94

CAP	L	W	H (Ref.)
> 1 x 4 Pin	10.0	5.0	7.0
≦ 1 x 4 Pin	5.0	4.0	2.6

Recommended PCB Layout
(PCB TOLERANCE ±0.1)

Old Part No. : PH1DM25-1XX-U

△x1	Add the package option	Alice	2022/04/26
△x2	ECN NO.:210916 Revise the drawing	Alice	2021/10/05
△	ECN No.:210619 Revise the top view	Alice	2021/09/17
REV.	ECN NO. OR DESCRIPTION	REVISED	DATE

Amtek Technology Co., Ltd.
TEL: 886-2-2260-6878
FAX: 886-2-2260-8030

品名 TITLE	PIN HEADER 2.54mm			頁數 Page	1/1
品號 PART NO.	5PH1DMA25-1XXXXNXXU -XXXXXXXXXX-00			繪圖 DRAWN	Jeff 2016/09/19
圖號 DRAWING NO.	GN016-GA117	版本 REV.	G	核對 CHECKED	Johnny 2016/09/19
客戶品號 CUSTOMER P/N		比例 SCALE	None	承認 APPROVED	Aaron 2016/09/19
公差 TOLERANCE	.X ± 0.38 .XX ± 0.25	單位 UNIT	mm	THIRD ANGLE PROJECTION	