




MATERIAL

Insulator: Nylon 9T, UL94V-0, Black
Contact Pin: Brass

ORDER INFORMATION

5 P H 1 K S A 2 5 - 2 X X X X N N X U - A B 000 - 0 0

2: Dual Row	No. of contacts Per Row(02~40)	G0: Gold Flash GA: Au 5u" GB: Au 10u" GC: Au 20u" GD: Au 30u" T0: Tin Plated	S0: Selective Au SA: Selective Au 5u" SB: Selective Au 10u" SC: Selective Au 20u" SD: Selective Au 30u" TE: Tin 200u"	N: Non Type N: W/O Peg	X: Box C: Tube With Cap	U: RoHS+Hi-Temp.	EX: 06003000 A: 6.0 B: 3.0
-------------	-----------------------------------	---	--	---------------------------	----------------------------	------------------	----------------------------------



Recommended PCB Layout
(PCB TOLERANCE ±0.1)

Old Part No.: PH1K25-2XX-U

 糧德精密有限公司 Amtek Technology Co., Ltd. TEL: 886-2-2260-6878 FAX: 886-2-2260-8030	品名 TITLE	PIN HEADER 2.54mm				頁數 Page	1/1
	品號 PART NO.	5PH1KSA25-2XXXXNNXU -XXXXXX000-00				繪圖 DRAWN	Mia 2015/08/18
	圖號 DRAWING NO.	GN016-GA125	版本 REV.	D	核對 CHECKED	John 2015/08/18	
	客戶品號 CUSTOMER P/N		比例 SCALE	None	承認 APPROVED	John 2015/08/18	
	公差 TOLERANCE	.X ± 0.35 .XX ± 0.25	.X±3	單位 UNIT	mm	THIRD ANGLE PROJECTION	

	ECN NO.:211018 Revise the drawing	Alice	2021/11/10
	QEC NO.:190504.:Revise the drawing	Nick	2019/05/30
	Modify order information	B	2017/01/24 Gary
REV.	ECN NO. OR DESCRIPTION	REVISED	DATE