

MATERIAL ⚠

Insulator: Nylon 9T, UL 94V-0
Contact Pin: Brass

ORDER INFORMATION

5PH2RDA15-4XX-XXNNXU-ABC-00

4:Quad Row

No. of contacts
Per Row(02~50)

G0:Gold Flash

GA:5u"

GB:10u"

GC:20u"

GD:30u"

T0:Tin Plated

S0:Selective Au

SA:5u"

SB:10u"

SC:20u"

SD:30u"

TE:200u"

N:Non Type

N:W/O Peg

X:Box

C:Tube With Cap

U:RoHS
+Hi-Temp.

B:Bag

EX:035024030

A:3.5

B:2.4

C:3.0

⚠

⚠

AMTEK 耀德
2023.05.11
Released DCC

Recommended PCB Layout
(PCB TOLERANCE ±0.05)

Old Part No. : PH2R15-4XX-U

REV.	ECN NO. OR DESCRIPTION	REVISED	DATE
⚠X1	ECN NO.:221005 Revise the drawing	Tim	2022/11/10
⚠	Modify order information	B	2017/02/02 Gary

耀德精密有限公司
Amtek Technology Co., Ltd.
TEL: 886-2-2260-6878
FAX: 886-2-2260-8030

品名 TITLE	PIN HEADER 2.0mm RIGHT ANGLE TYPE PLASTIC HEIGHT 1.5mm				頁數 Page	1/1
品號 PART NO.	5PH2RDA15-4XXXXNNXU -XXXXXX000-00				繪圖 DRAWN	Jeff 2016/09/08
圖號 DRAWING NO.	GW041-GA210	版本 REV.	C	核對 CHECKED	Johnny 2016/09/08	
客戶品號 CUSTOMER P/N		比例 SCALE	None	承認 APPROVED	Aaron 2016/09/08	
公差 TOLERANCE	.X ± 0.38 .XX ± 0.25	單位 UNIT	mm	THIRD ANGLE PROJECTION		