

MATERIAL

Insulator: Nylon 9T, UL94V-0, Black
Contact Pin: Brass

ORDER INFORMATION

5 P H 3 R D A 2 0 - 1 X X X X X X X U - A B C - 0 0

1:Single Row

No. of contacts
Per Row(02~50)

G0:Gold Flash
GA:5u"
GB:10u"
GC:20u"
GD:30u"
T0:Tin Plated

S0:Selective Au
SA:5u"
SB:10u"
SC:20u"
SD:30u"
TE:Tin 200u"




N:Non Type

RoHS

EX:040024030
A:4.0
B:2.4
C:3.0

N:W/O Peg

X:Box



Recommended PCB Layout
(PCB TOLERANCE ±0.05)

Old Part No. : PH3R20-1XX-U

ECN NO.:230707 Revise the drawing	Alice	2023/08/07
ECR No.191013>Delete the Package(C:Tube With Cap)	Nick	2019/10/28
ECN:170910,Delete the Packing:B:Bag	Kilin	2017/10/31
REV.	ECN NO. OR DESCRIPTION	REVISED DATE



Amtek Technology Co., Ltd.

TEL: 886-2-2260-6878
FAX: 886-2-2260-8030

品名 TITLE	PIN HEADER 1.27mm				頁數 Page	1/1
品號 PART NO.	5PH3RDA20-1XXXXXXXXU-XXXXXXXXXX-00				繪圖 DRAWN	Joey 2016/08/03
圖號 DRAWING NO.	GN110-GA306	版本 REV.	E	核對 CHECKED	Boris 2016/08/03	
客戶品號 CUSTOMER P/N		比例 SCALE	None	承認 APPROVED	Boris 2016/08/03	
公差 TOLERANCE	.X ± 0.25 .XX ± 0.20	單位 UNIT	mm	THIRD ANGLE PROJECTION		