


MATERIAL

Insulator: Nylon 9T, UL94V-0, Black
Contact Pin: Brass



ORDER INFORMATION

5 P H 3 S D A 1 7 - 2 X X X X X X X U - A B 000 - 0 0

2: Dual Row	No. of contacts Per Row(02~50)	G0: Gold Flash GA: 5u" GB: 10u" GC: 20u" GD: 30u" T0: Tin Plated	S0: Selective Au SA: 5u" SB: 10u" SC: 20u" SD: 30u" TE: Tin 200u"	N: Non Type	N: W/O Peg	RoHS	X: Box	EX: 040023000 A: 4.0 B: 2.3
-------------	-----------------------------------	---	--	-------------	------------	------	--------	-----------------------------------



Recommended PCB Layout
(PCB TOLERANCE ±0.05)



Old Part No. : PH3S17-2XX-U

△x1	ECN NO.:230707 Revise the drawing	Alice	2023/08/08
△x1	ECN No.:180310,Remove the Cap & Revise the Package option .	Roy	2018/03/23
△x1	ECN:170910,Delete the Packing:B:Bag	Kilin	2017/10/31
REV.	ECN NO. OR DESCRIPTION	REVISED	DATE



Amtek Technology Co., Ltd.
TEL: 886-2-2260-6878
FAX: 886-2-2260-8030

品名 TITLE	PIN HEADER 1.27mm D/R V/T DIP TYPE				頁數 Page	1/1
品號 PART NO.	5PH3SDA17- 2XXXXXXXU-XXXXXX000-00				繪圖 DRAWN	Roy 2015/08/18
圖號 DRAWING NO.	GN016-GA299	版本 REV.	E	核對 CHECKED	Josh 2018/03/23	
客戶品號 CUSTOMER P/N		比例 SCALE	None	承認 APPROVED	Jason 2018/03/23	
公差 TOLERANCE	.X ± 0.25 .XX ± 0.20	單位 UNIT	mm	THIRD ANGLE PROJECTION		