

ORDER INFORMATION

SPECIFICATION



Current Rating: 2 AMP
Insulation Resistance: 1000MΩ Min.
Contact Resistance: 20mΩ Max.
Dielectric Voltage: 500V AC for one minute
Operation Temperature:-40°C to +85°C

MATERIAL



Insulator:Hi-Temp. Thermoplastic, UL94V-0, Black
Contact Pin:Copper Alloy

5 P S 2 E S B 6 3 - 2 X X X X 5 X U 094023 - 0 0

2: Dual Row	No. of Pin Per Row(02~40)	G0:Gold Flash GA:5u" GB:10u" GC:20u" GD:30u" T0:Tin Plated TE:Tin 200u" S0:Selective SA:5u" SB:10u" SC:20u" SD:30u"	T:Tube X:Box	U:RoHS+Hi Temp
-------------	------------------------------	--	-------------------------------	----------------



Recommended PCB Layout
(PCB TOLERANCE ±0.1)



REV.	ECN NO. OR DESCRIPTION	REVISED	DATE

 糧德精密有限公司 Amtek Technology Co., Ltd. TEL: 886-2-2260-6878 FAX: 886-2-2260-8030	品名 TITLE	FEMALE HEADER 2.0mm			頁數 Page	1/1
	品號 PART NO.	5PS2ESB63-2XXXX5XU094023-00			繪圖 DRAWN	David 2019/10/21
	圖號 DRAWING NO.	GN147-DV422	版本 REV.	A	核對 CHECKED	Josh 2019/10/21
	客戶品號 CUSTOMER P/N		比例 SCALE	None	承認 APPROVED	Josh 2019/10/21
	公差 TOLERANCE	.X ± 0.38 .XX ± 0.25	.X° ± 3°	單位 UNIT	mm	THIRD ANGLE PROJECTION