

Electrical

Standard:  UL
Rated Voltage: 300V
Rated Current: 25A
Contact Resistance: 20mΩ
Insulation Resistance: 500MΩ / DC 500V
Wire Range: 22-12AWG 4.0mm²
Dielectric Voltage: AC 2000V for one minute
Temp. Range: -40°C ~ +105°C

Mechanical

Temp. Range: -40°C ~ +105°C
Torque: 0.8Nm

Material

Housing: Nylon 66, UL94V-0
Screws: M3.5, Steel, Ni Plated
Pin Header: Copper Alloy, Ni Plated

ORDER INFORMATION


5	T	B	1	1	0	N	-	6	9	M	E	X	X	B	L	X	-	W	1
Series No.							No. of Poles (02~26P)				B:Black		B:Bag A:Tray						



AMTEK 耀德

2021.01.13

Released DCC



linear dimension (Tolerances Standard GB/T 14486-2008)



<i>variable range</i>	to 6	over 6 to 10	over 10 to 30	over 30 to 60	over 60 to 100	over 100 to 160	over 160 to	to 10	over 10 to 100	over 100 to
<i>tolerance</i>	±0.20	±0.30	±0.50	±0.70	±1.00	±1.30	±1.60	0.10	0.30	0.60

 x2	ECN NO:201211 Revise the PART NO.	Alice	2020/12/31
 x1	ECN NO:200718 Revise the Tolerance	Alice	2020/11/06
 x1	ECN 200102: Remove the IEC	David	2020/03/21
REV.	ECN NO. OR DESCRIPTION	REVISED	DATE



品名 TITLE	11.0mm Terminal Block				頁數 Page	1/1
品號 PART NO.	 5TB110N-69MEXXB L X-W1				繪圖 DRAWN	Roy 2019/01/02
圖號 DRAWING NO.	GN011-R1092	版本 REV.	D	核對 CHECKED	Josh 2019/01/02	
客戶品號 CUSTOMER P/N		比例 SCALE	None	承認 APPROVED	Jason 2019/01/02	
公差 TOLERANCE		單位 UNIT	mm	THIRD ANGLE PROJECTION		