

Electrical

Standard: UL IEC
Rated Voltage: 300V 450V
Rated Current: 20A 24A
Contact Resistance: 20mΩ
Insulation Resistance: 500MΩ / DC 500V
Wire Range: 22-12AWG 2.5mm²
Dielectric Voltage: AC 2000V for one minute
Temp. Range: -40°C ~ +105°C

Mechanical

Torque: 1.2Nm

Material

Housing: Nylon 66, UL94V-0
Screws: M4.0, Steel, Ni Plated
Pin Header: Copper Alloy, Sn Plated
Cover: PC, UL94V-2

ORDER INFORMATION





5	T	B	1	1	0	R	-	6	8	R	N	X	X	B	L	X	-	W	1
Series No.								No. of Poles (02~22P)			B: Black		B: Bag A: Tray						



AMTEK 糧德

2021.01.13

Released DCC



linear dimension (Tolerances Standard GB/T 14486-2008)



variable range	to 6	over 6 to 10	over 10 to 30	over 30 to 60	over 60 to 100	over 100 to 160	over 160 to	to 10	over 10 to 100	over 100 to
tolerance	±0.20	±0.30	±0.50	±0.70	±1.00	±1.30	±1.60	0.10	0.30	0.60



ECN NO: 201211 Revise the PART NO.

Alice

2020/12/31



ECN NO: 200718 Revise the Tolerance

Alice

2020/11/09

REV.

ECN NO. OR DESCRIPTION

REVISED

DATE



糧德精密有限公司
Amtek Technology Co., Ltd.

TEL: 886-2-2260-6878
FAX: 886-2-2260-8030

品名 TITLE	11.0mm Terminal Block				頁數 Page	1/1
品號 PART NO.	△ 5TB110R-68RNXXBLX-W1				繪圖 DRAWN	Roy 2019/01/08
圖號 DRAWING NO.	GN011-R1134	版本 REV.	C	核對 CHECKED	Josh 2019/01/08	
客戶品號 CUSTOMER P/N		比例 SCALE	None	承認 APPROVED	Jason 2019/01/08	
公差 TOLERANCE		單位 UNIT	mm	THIRD ANGLE PROJECTION		