



Electrical 
Standard: UL
Rated Voltage: 600V
Rated Current: 40A
Contact Resistance: 20mΩ
Insulation Resistance: 500MΩ / DC 500V
Wire Range: 18-10AWG 6.0mm²
Dielectric Voltage: AC 2200V for one minute
Temp. Range: -40°C ~ +105°C


Mechanical
Torque: 1.2Nm

Material
Housing: Nylon 66, UL94V-0
Screws: M4.0, Steel, Ni Plated
Pin Header: Copper Alloy, Tin Plated
Cover: PC, UL94V-2



ORDER INFORMATION



Recommended PCB Layout



SECTION A-A



linear dimension(Tolerances Standard GB/T 14486-2008)								—	∠	⊥
variable range	to 6	over 6 to 10	over 10 to 30	over 30 to 60	over 60 to 100	over 100 to 160	over 160 to	to 10	over 10 to 100	over 100 to
tolerance	±0.20	±0.30	±0.50	±0.70	±1.00	±1.30	±1.60	0.10	0.30	0.60
	ECN NO:201211 Revise the PART NO							Alice	2021/01/04	
	ECN NO:200718 Revise the Tolerance							Alice	2020/11/11	
	ECN 200102: Remove the IEC							David	2020/06/06	
REV.	ECN NO. OR DESCRIPTION							REVISED	DATE	


糧德精密有限公司
Amtek Technology Co., Ltd.
TEL: 886-2-2260-6878
FAX: 886-2-2260-8030

品名 TITLE	13.0mm Terminal Block				頁數 Page	1/1
品號 PART NO.	 5TB130S-78HEXXBLX-W1				繪圖 DRAWN	Roy 2019/01/04
圖號 DRAWING NO.	GN011-R1122	版本 REV.	D	核對 CHECKED	Josh 2019/01/04	
客戶品號 CUSTOMER P/N		比例 SCALE	None	承認 APPROVED	Jason 2019/01/04	
公差 TOLERANCE		單位 UNIT	mm	THIRD ANGLE PROJECTION		