

ELECTRICAL

Standard:  UL
Rated Voltage: 300V
Rated Current: 15A
Contact Resistance: 20mΩ
Withstanding Voltage: AC 2000V for one min
Insulation Resistance: 500MΩ
Wire range: 22-14AWG 1.5mm²

MECHANICAL


Temp. Range: -40°C ~ +105°C
Torque: 0.5Nm

MATERIAL


Housing: PA66, UL94V-0
Screws: M3 Steel Ni plated
Pin header: Copper alloy, Tin plated

ORDER INFORMATION



5	T	B	7	6	2	S	-	2	5	R	N	X	X	B	L	X	-	W	1
Series No.								Poles (02-24P)			B:Black			A:Tray B:Bag					



Recommended PCB Layout



Section A-A



linear dimension(Tolerances Standard GB/T 14486-2008)



variable range	to 6	over 6 to 10	over 10 to 30	over 30 to 60	over 60 to 100	over 100 to 160	over 160 to 10	over 10 to 100	over 100 to 10	
tolerance	±0.20	±0.30	±0.50	±0.70	±1.00	±1.30	±1.60	0.10	0.30	0.60

 x2	ECN NO:201211 Revise the PART NO	Alice	2021/01/04
 x1	ECN NO:200718 Revise the Tolerance	Alice	2020/11/11
 x1	ECN 200102: Remove the IEC	David	2020/06/06
REV.	ECN NO. OR DESCRIPTION	REVISED	DATE


糧德精密有限公司
Amtek Technology Co., Ltd.
TEL: 886-2-2260-6878
FAX: 886-2-2260-8030

品名 TITLE	7.62mm TERMINAL BLOCK				頁數 Page	1/1
品號 PART NO.	 5TB762R-25RNXXBLX-W1				繪圖 DRAWN	Gary 2019/01/03
圖號 DRAWING NO.	GN011-GB755	版本 REV.	D	核對 CHECKED	Josh 2019/01/03	
客戶品號 CUSTOMER P/N		比例 SCALE	None	承認 APPROVED	Jason 2019/01/03	
公差 TOLERANCE		單位 UNIT	mm	THIRD ANGLE PROJECTION		