

ELECTRICAL

Standard: UL
Rated Voltage: 300V
Rated Current: 15A
Contact Resistance: 20mΩ
Withstanding Voltage: AC 2000V for one min
Insulation Resistance: 500MΩ
Wire range: 22-14AWG 1.5mm²

MECHANICAL

Temp. Range: -40°C ~ +105°C
Torque: 0.5Nm

MATERIAL

Housing: PA66, UL94V-0
Screws: M3.0 Steel Ni plated
Pin header: Copper alloy, Tin plated
Cover: PC, UL94V-2

ORDER INFORMATION

5 T B 8 2 5 R - 3 8 R N X X B L X - W 1

Series No.

Poles
(02-22P)


B:Black

A:Tray
B:Bag


AMTEK 糧德

2021.01.13



Released DCC



Recommended PCB Layout



SECTION A-A




linear dimension(Tolerances Standard GB/T 14486-2008)



variable range	to 6	over 6 to 10	over 10 to 30	over 30 to 60	over 60 to 100	over 100 to 160	over 160 to 10	over 10 to 100	over 100 to 100	
tolerance	±0.20	±0.30	±0.50	±0.70	±1.00	±1.30	±1.60	0.10	0.30	0.60

	ECN NO:201211 Revise the PART NO	Alice	2021/01/04
	ECN NO:200718 Revise the Tolerance	Alice	2020/11/30
	ECN 200102: Remove the IEC	David	2020/06/11
REV.	ECN NO. OR DESCRIPTION	REVISED	DATE



品名 TITLE	8.25mm Terminal Block				頁數 Page	1/1
品號 PART NO.	 5TB825R-38RNXXBLX-W1			繪圖 DRAWN	Eric 2019/01/10	
圖號 DRAWING NO.	GN011-EA544		版本 REV.	D	核對 CHECKED	Josh 2019/01/10
客戶品號 CUSTOMER P/N			比例 SCALE	None	承認 APPROVED	Jason 2019/01/10
公差 TOLERANCE			單位 UNIT	mm	THIRD ANGLE PROJECTION	