


Electrical △B
Standard: UL
Rated Voltage: 300V
Rated Current: 20A
Contact Resistance: 20mΩ
Insulation Resistance: 500MΩ / DC 500V
Wire Range: 22-14AWG 1.5mm²
Dielectric Voltage: AC 2000V for one minute
Temp. Range: -40°C ~ +105°C

Mechanical
Torque: 0.5Nm


Material
Housing: Nylon 66, UL94V-0
Screws: M3.0, Steel, Ni Plated
Pin Header: Copper Alloy, Tin Plated

ORDER INFORMATION


5	T	B	8	5	0	S	-	J	2	6	N	X	X	B	L	X	-	W	1
Series No.								No. of Poles (02~26P)			B:Black		B:Bag A:Tray						



Recommended PCB Layout



SECTION A-A



linear dimension(Tolerances Standard GB/T 14486-2008)



variable range	to 6	over 6 to 10	over 10 to 30	over 30 to 60	over 60 to 100	over 100 to 160	over 160 to	to 10	over 10 to 100	over 100 to
tolerance	±0.20	±0.30	±0.50	±0.70	±1.00	±1.30	±1.60	0.10	0.30	0.60

△C x3	ECN NO:200718 Revise the Tolerance & ECN NO:201211 Revise the PART NO.	Alice	2020/12/22
△B x1	ECN 200102: Remove the IEC	David	2020/06/06
REV.	ECN NO. OR DESCRIPTION	REVISED	DATE



品名 TITLE	8.50mm Terminal Block				頁數 Page	1/1
品號 PART NO.	△C 5TB850S-J26NXXBLX-W1			繪圖 DRAWN	Roy 2019/01/04	
圖號 DRAWING NO.	GN011-R1117	版本 REV.	C	核對 CHECKED	Josh 2019/01/04	
客戶品號 CUSTOMER P/N		比例 SCALE	None	承認 APPROVED	Jason 2019/01/04	
公差 TOLERANCE		單位 UNIT	mm	THIRD ANGLE PROJECTION		