

ELECTRICAL

Standard: UL IEC
Rated Voltage: 300V 450V
Rated Current: 26A 24A
Contact Resistance: 20mΩ
Withstanding Voltage: AC 2000V for one min
Insulation Resistance: 500MΩ
Wire range: 20-10AWG 6mm²

MECHANICAL



Temp. Range: -40°C ~ +105°C
Torque: 0.5Nm
Steip length: 7-8mm

MATERIAL

Housing: PA66, UL94V-2
Screws: M3 Steel, Zn plated
Copper Cylinder: Copper alloy, Zn plated

ORDER INFORMATION

5	T	F	1	0	0	N	-	0	H	S	A	X	X	G	L	X	-	0	1
Series No.								Poles (02-12P)				G:Gray			A:Tray B:Bag				



SECTION A-A

AMTEK 耀德
2023.11.02
Released DCC

linear dimension (Tolerances Standard GB/T 14486-2008)



variable range	to 6	over 6 to 10	over 10 to 30	over 30 to 60	over 60 to 100	over 100 to 160	over 160 to 10	to 10	over 10 to 100	over 100 to 100
tolerance	±0.20	±0.30	±0.50	±0.70	±1.00	±1.30	±1.60	0.10	0.30	0.60

△	ECN NO:230714 Revise the PART NO.	Benson	2023/08/29
△x2	ECN NO:201210 Revise the PART NO.	Alice	2020/12/18
△x1	ECN NO:200718 Revise the Tolerance	Alice	2020/09/30
REV.	ECN NO. OR DESCRIPTION	REVISED	DATE



耀德精密有限公司
Amtek Technology Co., Ltd.
TEL: 886-2-2260-6878
FAX: 886-2-2260-8030

品名 TITLE	10.0mm Terminal Block				頁數 Page	1/1
品號 PART NO.	△ 5TF100N-OHSAXXWLX-01				繪圖 DRAWN	Eric 2018/12/27
圖號 DRAWING NO.	GN011-EA412		版本 REV.	D	核對 CHECKED	Josh 2018/12/27
客戶品號 CUSTOMER P/N			比例 SCALE	None	承認 APPROVED	Jason 2018/12/27
公差 TOLERANCE			單位 UNIT	mm	THIRD ANGLE PROJECTION	