

ELECTRICAL

Standard: UL IEC
Rated Voltage: 600V 750V
Rated Current: 15A 17.5A
Contact Resistance: 20mΩ
Withstanding Voltage: AC 2000V for one min
Insulation Resistance: 500MΩ
Wire range: 22-14AWG 1.5mm²

MECHANICAL



Temp. Range: -40°C ~ +105°C
Torque: 0.4Nm
Steip length: 7-8mm

MATERIAL

Housing: PA66, UL94V-2
Screws: M2.5 Steel, Zn plated
Copper Cylinder: Brass, Ni plated

ORDER INFORMATION

5	T	F	8	0	0	N	-	Y	8	H	A	X	X	X	L	X	-	0	1
Series No.								Poles (02-12P)				G:Gray			A:Tray B:Bag				



SECTION A-A

AMTEK糧德

2023.11.02

Released DCC



linear dimension(Tolerances Standard GB/T 14486-2008)								—	∇	⊥
variable range	to 6	over 6 to 10	over 10 to 30	over 30 to 60	over 60 to 100	over 100 to 160	over 160 to	to 10	over 10 to 100	over 100 to
tolerance	±0.20	±0.30	±0.50	±0.70	±1.00	±1.30	±1.60	0.10	0.30	0.60
△	ECN NO:230714 Revise the PART NO.							Alice	2023/09/23	
△x2	ECN NO:201210 Revise the PART NO.							Alice	2020/12/18	
△x1	ECN NO:200718 Revise the Tolerance							Alice	2020/09/30	
REV.	ECN NO. OR DESCRIPTION							REVISED	DATE	



糧德精密有限公司
Amtek Technology Co., Ltd.
TEL: 886-2-2260-6878
FAX: 886-2-2260-8030

品名 TITLE	8.0mm Terminal Block				頁數 Page	1/1
品號 PART NO.	△△ 5TF800N-Y8HAXXXLX-01			繪圖 DRAWN	Eric 2018/12/27	
圖號 DRAWING NO.	GN011-EA413		版本 REV.	D	核對 CHECKED	Josh 2018/12/27
客戶品號 CUSTOMER P/N			比例 SCALE	None	承認 APPROVED	Jason 2018/12/27
公差 TOLERANCE			單位 UNIT	mm	THIRD ANGLE PROJECTION	