

ELECTRICAL

Standard: UL IEC
Rated Voltage: 300V 130V
Rated Current: 10A 10A
Contact Resistance: 20mΩ
Insulation Resistance: 500MΩ / DC 500V
Wire Rang: 28~14AWG 1.5mm²
Withstanding Voltage: AC 2000V for one minute

MECHANICAL

Steip Length: 8-9mm
Temp. Range: -40°C~+105°C

Dimensions

Pitch: 3.81mm
Poles: 2-24P

MATERIAL

Housing: PA66, UL94V-0
Wire guard: Stainless Steel
Pin header: Copper alloy, Sn plated

ORDER INFORMATION

5 T M 3 8 1 N - W 0 2 F X X O L X - 0 1

No of Poles
(02~24)

O: Orange



A: Tray
B: Bag




AMTEK 耀德

2020.11.04



Released DCC



3.81XX+11.8(REF)



3.81



linear dimension (Tolerances Standard GB/T 14486-2008)



<i>variable range</i>	to 6	over 6 to 10	over 10 to 30	over 30 to 60	over 60 to 100	over 100 to 160	over 160 to	to 10	over 10 to 100	over 100 to
<i>tolerance</i>	±0.20	±0.30	±0.50	±0.70	±1.00	±1.30	±1.60	0.10	0.30	0.60



ECN NO: 200718 Revise the Tolerance

Alice

2020/10/29

REV.

ECN NO. OR DESCRIPTION

REVISED

DATE



耀德精密有限公司
Amtek Technology Co., Ltd.

TEL: 886-2-2260-6878
FAX: 886-2-2260-8030

品名 TITLE	3.81mm Terminal Block				頁數 Page	1/1
品號 PART NO.	5TM381N-W02FXXOLX-01			繪圖 DRAWN	Nick 2020/01/14	
圖號 DRAWING NO.	GN011-NI758	版本 REV.	B	核對 CHECKED	Josh 2020/01/14	
客戶品號 CUSTOMER P/N		比例 SCALE	None	承認 APPROVED	Josh 2020/01/14	
公差 TOLERANCE		單位 UNIT	mm	THIRD ANGLE PROJECTION		