

ELECTRICAL

Standard: UL IEC
Rated Voltage: 300V 250V
Rated Current: 15A 16A
Contact Resistance:20mΩ
Insulation Resistance: 500MΩ / DC 500V
Wire Rang:28~12AWG 2.5mm²
Withstanding Voltage: AC 2000V for one minute

MECHANICAL

Steip Length:8-9mm
Temp.Range:-40°C~+105°C

Dimensions







Pitch:5.08mm
Poles:2-24P

MATERIAL

Housing: PA66, UL94V-0
Wire guard:Stainless Steel
Pin header:Copper alloy ,Sn plated

ORDER INFORMATION

5 T M 5 0 8 N - J 0 5 N X X O L X - 0 1



linear dimension(Tolerances Standard GB/T 14486-2008)



variable range	to 6	over 6 to 10	over 10 to 30	over 30 to 60	over 60 to 100	over 100 to 160	over 160 to	to 10	over 10 to 100	over 100 to
tolerance	±0.20	±0.30	±0.50	±0.70	±1.00	±1.30	±1.60	0.10	0.30	0.60



ECN NO:200718 Revise the Tolerance

Alice

2020/11/02

REV.

ECN NO. OR DESCRIPTION

REVISED

DATE



糧德精密有限公司
Amtek Technology Co., Ltd.

TEL: 886-2-2260-6878
FAX: 886-2-2260-8030

品名 TITLE	Terminal Block				頁數 Page	1/1
品號 PART NO.	5TM508N-J05NXXOLX-01				繪圖 DRAWN	Nick 2020/02/05
圖號 DRAWING NO.	GN011-NI794	版本 REV.	B	核對 CHECKED	Josh 2020/02/05	
客戶品號 CUSTOMER P/N		比例 SCALE	None	承認 APPROVED	Josh 2020/02/05	
公差 TOLERANCE		單位 UNIT	mm	THIRD ANGLE PROJECTION		