


Standard:	UL	IEC
Rated Voltage:	300V	250V
Rated Current:	15A	16A
Contact Resistance:	20mΩ	
Withstanding Voltage:	AC 2000V	
Insulation Resistance:	500MΩ	

ORDER INFORMATION




\MECHANICAL

Temp. Range: -40°C ~ +105°C




MATERIAL

Housing: PA66, UL94V-0

Pin header: Copper alloy, Sn plated



Recommended PCB Layout



linear dimension(Tolerances Standard GB/T 14486-2008)



<i>variable range</i>	to 6	over 6 to 10	over 10 to 30	over 30 to 60	over 60 to 100	over 100 to 160	over 160 to	to 10	over 10 to 100	over 100 to
<i>tolerance</i>	±0.20	±0.30	±0.50	±0.70	±1.00	±1.30	±1.60	0.10	0.30	0.60



REV.	ECN NO. OR DESCRIPTION	REVISED	DATE
Bx1	ECN NO:200718 Revise the Tolerance	Alice	2020/11/02



糧德精密有限公司
Amtek Technology Co., Ltd.

TEL: 886-2-2260-6878
FAX: 886-2-2260-8030

品名 TITLE	5.08mm Terminal Block				頁數 Page	1/1
品號 PART NO.	5TM508R-W04NXXOLX-01			繪圖 DRAWN	Eric 2019/01/03	
圖號 DRAWING NO.	GN011-EA448	版本 REV.	B	核對 CHECKED	Josh 2019/01/03	
客戶品號 CUSTOMER P/N		比例 SCALE	None	承認 APPROVED	Jason 2019/01/03	
公差 TOLERANCE		單位 UNIT	mm	THIRD ANGLE PROJECTION		