

ELECTRICAL

Standard: UL IEC
 Rated Voltage: 300V 250V
 Rated Current: 15A 16A
 Contact Resistance: 20mΩ
 Withstanding Voltage: AC 2000V for one min
 Insulation Resistance: 500MΩ

MECHANICAL

Temp. Range: -40°C ~ +105°C

MATERIAL

Housing: PA66, UL94V-0
 Pin header: Copper alloy, Sn plated




ORDER INFORMATION

5 T M 5 0 8 S - W 0 1 N X X O L X - 0 1

Series No.

Poles
(02-24P)

O:Orange

A:Tray
B:Bag

AMTEK 糧德

2020.11.11

Released DCC



linear dimension (Tolerances Standard GB/T 14486-2008)



variable range	to 6	over 6 to 10	over 10 to 30	over 30 to 60	over 60 to 100	over 100 to 160	over 160 to 250	to 10	over 10 to 100	over 100 to 250
tolerance	±0.20	±0.30	±0.50	±0.70	±1.00	±1.30	±1.60	0.10	0.30	0.60

糧德精密有限公司
 Amtek Technology Co., Ltd.
 TEL: 886-2-2260-6878
 FAX: 886-2-2260-8030

品名 TITLE	5.08mm Terminal Block				頁數 Page	1/1
品號 PART NO.	5TM508S-W01NXXOLX-01				繪圖 DRAWN	Eric 2019/01/03
圖號 DRAWING NO.	GN011-EA442		版本 REV.	B	核對 CHECKED	Josh 2019/01/03
客戶品號 CUSTOMER P/N			比例 SCALE	None	承認 APPROVED	Jason 2019/01/03
公差 TOLERANCE			單位 UNIT	mm	THIRD ANGLE PROJECTION	

ECN NO:200718 Revise the Tolerance

Alice

2020/11/03

ECN NO. OR DESCRIPTION

REVISED

DATE

REV.