

ELECTRICAL

Standard: UL IEC
 Rated Voltage: 300V 250V
 Rated Current: 15A 12A
 Contact Resistance: 20mΩ
 Withstanding Voltage: AC 2000V for one min
 Insulation Resistance: 500MΩ
 Wire range: 28-12AWG 2.5mm²

MECHANICAL

Temp. Range: -40°C ~ +105°C
 Steip length: 8-9mm

MATERIAL

Housing: PA66, UL94V-0
 Clamp: Phosphor bronze, Tin plated
 Wire guard: Stainless steel




ORDER INFORMATION

5 T M 7 5 0 N - W 0 4 N X X G L X - 0 1

Series No.

Poles
(02-24P)

G:Gray

A:Tray
B:Bag

linear dimension(Tolerances Standard GB/T 14486-2008)



variable range	to 6	over 6 to 10	over 10 to 30	over 30 to 60	over 60 to 100	over 100 to 160	over 160 to 100	to 10	over 10 to 100	over 100 to 100
tolerance	±0.20	±0.30	±0.50	±0.70	±1.00	±1.30	±1.60	0.10	0.30	0.60

REV.	ECN NO.200718 Revise the Tolerance	Alice	2020/11/03
	ECN NO. OR DESCRIPTION	REVISED	DATE

AMTEK
 糧德精密有限公司
 Amtek Technology Co., Ltd.
 TEL: 886-2-2260-6878
 FAX: 886-2-2260-8030

品名 TITLE	7.5mm Terminal Block				頁數 Page	1/1
品號 PART NO.	5TM750N-W04NXXGLX-01				繪圖 DRAWN	Eric 2019/01/03
圖號 DRAWING NO.	GN011-EA434	版本 REV.	B	核對 CHECKED	承認 APPROVED	Josh 2019/01/03
客戶品號 CUSTOMER P/N		比例 SCALE	None	承認 APPROVED	承認 APPROVED	Jason 2019/01/03
公差 TOLERANCE		單位 UNIT	mm	THIRD ANGLE PROJECTION		