

ELECTRICAL

Standard: UL IEC
 Rated Voltage: 300V 250V
 Rated Current: 15A 16A
 Contact Resistance: 20mΩ
 Withstanding Voltage: AC 2000V for one min
 Insulation Resistance: 500MΩ
 Wire range: 28-12AWG 2.5mm²

MECHANICAL

Temp. Range: -40°C ~ +105°C
 Steip length: 8-9mm

MATERIAL

Housing: PA66, UL94V-0
 Clamp: Copper alloy, Sn plated
 Wire guard: Stainless steel




ORDER INFORMATION

5 T M 7 6 2 N - W 0 3 N X X O L X - 0 1

Series No.

Poles
(02-24P)

O:Orange

A:Tray
B:Bag

linear dimension (Tolerances Standard GB/T 14486-2008)



variable range	to 6	over 6 to 10	over 10 to 30	over 30 to 60	over 60 to 100	over 100 to 160	over 160 to	to 10	over 10 to 100	over 100 to
tolerance	±0.20	±0.30	±0.50	±0.70	±1.00	±1.30	±1.60	0.10	0.30	0.60

糧德精密有限公司
 Amtek Technology Co., Ltd.
 TEL: 886-2-2260-6878
 FAX: 886-2-2260-8030

品名 TITLE	7.62mm Terminal Block				頁數 Page	1/1
品號 PART NO.	5TM762N-W03NXXOLX-01				繪圖 DRAWN	Eric 2019/01/03
圖號 DRAWING NO.	GN011-EA433				版本 REV.	B
客戶品號 CUSTOMER P/N					核對 CHECKED	Josh 2019/01/03
公差 TOLERANCE					比例 SCALE	None
					承認 APPROVED	Jason 2019/01/03
					單位 UNIT	mm
					THIRD ANGLE PROJECTION	

ECN NO:200718 Revise the Tolerance

Alice

2020/11/04

ECN NO. OR DESCRIPTION

REVISED

DATE



REV.