

ELECTRICAL

Standard: UL IEC
 Rated Voltage: 300V 250V
 Rated Current: 8A 8A

Contact Resistance: 20mΩ

Withstanding Voltage: AC 2000V for one min

Insulation Resistance: 500MΩ

Wire range: 24-16AWG 1 mm²

MECHANICAL

Temp. Range: -40°C ~ +105°C

Strip length: 9-10mm

MATERIAL

Housing: PA66, UL94V-0

Clamp: Copper alloy, Sn plated

Shrapnel: stainless steel

ORDER INFORMATION

5 T P 3 5 0 N -

5 G B

F X X

X L





X - 0 1

Series No.

No of Pins total
(04~48P)

E:Green

A:Tray
B:Bag



linear dimension(Tolerances Standard GB/T 14486-2008)



variable range	to 6	over 6 to 10	over 10 to 30	over 30 to 60	over 60 to 100	over 100 to 160	over 160 to	to 10	over 10 to 100	over 100 to
tolerance	±0.20	±0.30	±0.50	±0.70	±1.00	±1.30	±1.60	0.10	0.30	0.60

△E	ECN NO.: 230714 Revise the PART NO	Randy	2023/09/23
△x1	ECN NO:220814 Revise the PART NO.	Tim	2022/09/16
△x2	ECN NO:201224 Revise the PART NO.	Alice	2021/01/13
REV.	ECN NO. OR DESCRIPTION	REVISED	DATE

AMTEK
 糧德精密有限公司
 Amtek Technology Co., Ltd.
 TEL: 886-2-2260-6878
 FAX: 886-2-2260-8030

品名 TITLE	3.5mm Terminal Block				頁數 Page	1/1
品號 PART NO.	△ 5TP350N-5GBFXXXLX-01 △				繪圖 DRAWN	Eric 2018/11/26
圖號 DRAWING NO.	GN011-EA100		版本 REV.	E	核對 CHECKED	Josh 2018/11/26
客戶品號 CUSTOMER P/N			比例 SCALE	None	承認 APPROVED	Jason 2018/11/26
公差 TOLERANCE			單位 UNIT	mm	THIRD ANGLE PROJECTION	