

ELECTRICAL

Standard: UL IEC
Rated Voltage: 300V 160V
Rated Current: 8A 7A
Contact Resistance: 20mΩ
Withstanding Voltage: AC 1600V for one min
Insulation Resistance: 500MΩ

MECHANICAL

Temp. Range: -40°C ~ +105°C

MATERIAL

Housing: PA66, UL94V-0
Contactor: Copper alloy, Sn plated

ORDER INFORMATION

5 T P 3 5 0 R -

5 D T E X X E L X - 0 1

Series No.

No of Pins total
(04~48P)

E:Green


A:Tray
B:Bag






AMTEK 糧德

2022.09.30

Released DCC



Recommended PCB Layout



SECTION:P-P

linear dimension(Tolerances Standard GB/T 14486-2008)



variable range	to 6	over 6 to 10	over 10 to 30	over 30 to 60	over 60 to 100	over 100 to 160	over 160 to	to 10	over 10 to 100	over 100 to
tolerance	±0.20	±0.30	±0.50	±0.70	±1.00	±1.30	±1.60	0.10	0.30	0.60

△x1	ECN NO:220814 Revise the PART NO.	Tim	2022/09/16
△x1	ECN NO:200718 Revise the Dimension	Alice	2020/09/04
REV.	ECN NO. OR DESCRIPTION	REVISED	DATE



糧德精密有限公司
Amtek Technology Co., Ltd.

TEL: 886-2-2260-6878
FAX: 886-2-2260-8030

品名 TITLE	3.50mm Terminal Block				頁數 Page	1/1
品號 PART NO.	5TP350R-5DTEXXELX-01				繪圖 DRAWN	Eric 2018/12/17
圖號 DRAWING NO.	GN011-EA298	版本 REV.	C	核對 CHECKED	Josh 2018/12/17	
客戶品號 CUSTOMER P/N		比例 SCALE	None	承認 APPROVED	Jason 2018/12/17	
公差 TOLERANCE		單位 UNIT	mm	THIRD ANGLE PROJECTION		