

ELECTRICAL

Standard: UL IEC
 Rated Voltage: 300V 250V
 Rated Current: 8A 10A
 Contact Resistance: 20mΩ
 Withstanding Voltage: AC 2000V for one min
 Insulation Resistance: 500MΩ

MECHANICAL




Temp. Range: -40°C ~ +105°C

MATERIAL

Housing: High temperature polyamide, UL94V-0
 Pin header: Copper alloy, Sn plated

ORDER INFORMATION

5 T P 3 8 1 S - 5 E C N X X B U X - 0 1



B

linear dimension (Tolerances Standard GB/T 14486-2008)

variable range	to 6	over 6 to 10	over 10 to 30	over 30 to 60	over 60 to 100	over 100 to 160	to 10	over 10 to 100	over 100 to 160	
tolerance	±0.20	±0.30	±0.50	±0.70	±1.00	±1.30	±1.60	0.10	0.30	0.60

REV.	ECN NO. OR DESCRIPTION	REVISED	DATE
B x1	ECN NO.:200718 Revise the Tolerance	Alice	2020/09/10

糧德精密有限公司
 Amtek Technology Co., Ltd.
 TEL: 886-2-2260-6878
 FAX: 886-2-2260-8030

品名 TITLE	3.81mm Terminal Block				頁數 Page	1/1
品號 PART NO.	5TP381S-5ECNXXBUX-01			繪圖 DRAWN	Eric 2018/11/26	
圖號 DRAWING NO.	GN011-EA101	版本 REV.	B	核對 CHECKED	Josh 2018/11/26	
客戶品號 CUSTOMER P/N		比例 SCALE	None	承認 APPROVED	Jason 2018/11/26	
公差 TOLERANCE		單位 UNIT	mm	THIRD ANGLE PROJECTION		