

ELECTRICAL

Standard: UL IEC
Rated Voltage: 300V 320V
Rated Current: 10A 10A
Contact Resistance: 20mΩ
Withstanding Voltage: AC 2000V for one min
Insulation Resistance: 500MΩ
Wire range: 28-12AWG 2.5mm²


MECHANICAL

Temp. Range: -40°C ~ +105°C
Steip length: 7-8mm

MATERIAL

Housing: PA66, UL94V-0
Clamp: Copper alloy, Sn plated
Shrapnel: Stainless steel




ORDER INFORMATION



AMTEK 糧德

2023.11.02

Released DCC



linear dimension(Tolerances Standard GB/T 14486-2008)

variable range	to 6	over 6 to 10	over 10 to 30	over 30 to 60	over 60 to 100	over 100 to 160	over 160 to 10	over 10 to 100	over 100 to 100
tolerance	±0.20	±0.30	±0.50	±0.70	±1.00	±1.30	±1.60	0.10	0.30

△	ECN NO:230714 Revise the PART NO.	Gaby	2023/09/21
△x2	ECN NO:201215 Revise the PART NO.	Alice	2020/12/30
△x1	ECN NO:200718 Revise the Tolerance	Alice	2020/09/16
REV.	ECN NO. OR DESCRIPTION	REVISED	DATE



糧德精密有限公司
Amtek Technology Co., Ltd.
TEL: 886-2-2260-6878
FAX: 886-2-2260-8030

品名 TITLE	5.0mm Terminal Block				頁數 Page	1/1
品號 PART NO.	△ 5TP500N-2KRGXXXLX-01 △				繪圖 DRAWN	Eric 2018/12/06
圖號 DRAWING NO.	GN011-EA197				版本 REV.	D
客戶品號 CUSTOMER P/N					核對 CHECKED	Josh 2018/12/06
公差 TOLERANCE					承認 APPROVED	Jason 2018/12/06
					比例 SCALE	None
					單位 UNIT	mm
					THIRD ANGLE PROJECTION	