

ELECTRICAL

Standard: UL IEC
 Rated Voltage: 300V 450V
 Rated Current: 15A 20A
 Contact Resistance: 20mΩ
 Withstanding Voltage: AC 2000V for one min
 Insulation Resistance: 500MΩ
 Wire range: 28-14AWG 2.5mm²

MECHANICAL

Temp. Range: -40°C ~ +105°C
 Steip length: 7-8mm

MATERIAL

Housing: PA66, UL94V-0
 Screws: M3 steel, Zn plated
 Pin header: Brass, Ni plated
 Cage: Brass, Ni plated
 Nut: Brass




ORDER INFORMATION

5 T P 5 0 8 N - 2 G B E X X E L X - 0 1

Series No.

Poles
(02-24P)

E:Green

A:Tray
B:Bag

linear dimension(Tolerances Standard GB/T 14486-2008)



variable range	to 6	over 6 to 10	over 10 to 30	over 30 to 60	over 60 to 100	over 100 to 160	over 160 to 1000	to 10	over 10 to 100	over 100 to 1000
tolerance	±0.20	±0.30	±0.50	±0.70	±1.00	±1.30	±1.60	0.10	0.30	0.60

糧德精密有限公司
 Amtek Technology Co., Ltd.
 TEL: 886-2-2260-6878
 FAX: 886-2-2260-8030

品名 TITLE	5.08mm Terminal Block				頁數 Page	1/1
品號 PART NO.	5TP508N-2GBEXXELX-01				繪圖 DRAWN	Eric 2018/12/07
圖號 DRAWING NO.	GN011-EA214		版本 REV.	B	核對 CHECKED	Josh 2018/12/07
客戶品號 CUSTOMER P/N			比例 SCALE	None	承認 APPROVED	Jason 2018/12/07
公差 TOLERANCE			單位 UNIT	mm	THIRD ANGLE PROJECTION	



ECN NO:200718 Revise the Tolerance

Alice

2020/09/18

ECN NO. OR DESCRIPTION

REVISED

DATE