


**ELECTRICAL**

Standard: UL IEC  
 Rated Voltage: 300V 450V  
 Rated Current: 15A 17.5A  
 Contact Resistance: 20mΩ  
 Withstanding Voltage: AC 2000V for one min  
 Insulation Resistance: 500MΩ  
 Wire range: 28-14AWG 1.5mm<sup>2</sup>

**ORDER INFORMATION**

5 T P 5 0 8 N - 2 K B E X X E L X - 0 1







**MECHANICAL**

Temp. Range: -40°C ~ +105°C  
 Torque: 0.5Nm

Steip length: 7-8mm

**MATERIAL**

Housing: PA66, UL94V-0  
 Screws: M3, Steel, Zn plated  
 C;amp: Phosphor bronze, Ni plated  
 Cage: Brass, Ni plated



linear dimension(Tolerances Standard GB/T 14486-2008)								—	▯	⊥
variable range	to 6	over 6 to 10	over 10 to 30	over 30 to 60	over 60 to 100	over 100 to 160	over 160 to 10	over 10 to 100	over 100 to 100	
tolerance	±0.20	±0.30	±0.50	±0.70	±1.00	±1.30	±1.60	0.10	0.30	0.60

REV.	ECN NO. OR DESCRIPTION	REVISED	DATE
B.1	ECN NO:200718 Revise the Tolerance	Alice	2020/09/18

**糧德精密有限公司**  
 Amtek Technology Co., Ltd.  
 TEL: 886-2-2260-6878  
 FAX: 886-2-2260-8030

品名 TITLE	5.08mm Terminal Block				頁數 Page	1/1
品號 PART NO.	5TP508N-2KBEXXELX-01			繪圖 DRAWN	Eric 2018/12/18	
圖號 DRAWING NO.	GN011-EA316		版本 REV.	B	核對 CHECKED	Josh 2018/12/18
客戶品號 CUSTOMER P/N			比例 SCALE	None	承認 APPROVED	Jason 2018/12/18
公差 TOLERANCE			單位 UNIT	mm	THIRD ANGLE PROJECTION	