

ELECTRICAL

Standard: UL IEC
Rated Voltage: 300V 320V
Rated Current: 10A 10A
Contact Resistance: 20mΩ
Withstanding Voltage: AC 2000V for one min
Insulation Resistance: 500MΩ
Wire range: 28-12AWG 2.5mm²

MECHANICAL




Temp. Range: -40°C ~ +105°C
Steip length: 7-8mm

MATERIAL

Housing: PA66, UL94V-0
Clamp: Copper alloy, Sn plated
Shrapnel: Stainless steel

ORDER INFORMATION

5	T	P	5	0	8	N	-	2	K	R	E	X	X	X	L	X	-	0	1
Series No.								Poles (02-24P)			E:Green			A:Tray B:Bag					



linear dimension(Tolerances Standard GB/T 14486-2008)



variable range	to 6	over 6 to 10	over 10 to 30	over 30 to 60	over 60 to 100	over 100 to 160	over 160 to 10	over 10 to 100	over 100 to 100	
tolerance	±0.20	±0.30	±0.50	±0.70	±1.00	±1.30	±1.60	0.10	0.30	0.60

△	ECN NO:230714 Revise the PART NO.	Gaby	2023/09/23
△x2	ECN NO:201215 Revise the PART NO.	Alice	2020/12/30
△x1	ECN NO:200718 Revise the Tolerance	Alice	2020/09/23
REV.	ECN NO. OR DESCRIPTION	REVISED	DATE



糧德精密有限公司
Amtek Technology Co., Ltd.
TEL: 886-2-2260-6878
FAX: 886-2-2260-8030

TITLE		5.0mm Terminal Block				Page	1/1
品號 PART NO.	△ 5TP508N-2KREXXXLX-01 △	繪圖 DRAWN	Eric 2018/12/06				
圖號 DRAWING NO.	GN011-EA196	版本 REV.	D	核對 CHECKED	Josh 2018/12/06		
客戶品號 CUSTOMER P/N		比例 SCALE	None	承認 APPROVED	Jason 2018/12/06		
公差 TOLERANCE		單位 UNIT	mm	THIRD ANGLE PROJECTION			