

ELECTRICAL

Standard: UL IEC
 Rated Voltage: 300V 450V
 Rated Current: 15A 20A
 Contact Resistance: 20mΩ
 Withstanding Voltage: AC 2000V for one min
 Insulation Resistance: 500MΩ
 Wire range: 28-14AWG 2.5mm²

MECHANICAL

Temp. Range: -40°C ~ +105°C
 Torque: 0.5Nm
 Steip length: 7-8mm

MATERIAL

Housing: PA66, UL94V-0
 Screws: M3 steel, Zn plated
 Pin header: Brass, Tin plated
 Cage: Brass, Ni plated

ORDER INFORMATION

5 T P 5 0 8 N -

2 R E N X X


X L

X - 0 1


Series No.

Poles
(06-24P)

E:Green

A:Tray
B:Bag

AMTEK 耀德
 2023.11.02
 Released DCC



linear dimension(Tolerances Standard GB/T 14486-2008)



variable range	to 6	over 6 to 10	over 10 to 30	over 30 to 60	over 60 to 100	over 100 to 160	over 160 to	to 10	over 10 to 100	over 100 to
tolerance	±0.20	±0.30	±0.50	±0.70	±1.00	±1.30	±1.60	0.10	0.30	0.60

△	ECN NO:230714 Revise the PART NO.	Gaby	2023/09/23
△x2	ECN NO:201215 Revise the PART NO.	Alice	2020/12/30
△x1	ECN NO:200718 Revise the Tolerance	Alice	2020/09/23
REV.	ECN NO. OR DESCRIPTION	REVISED	DATE

AMTEK
 耀德精密有限公司
 Amtek Technology Co., Ltd.
 TEL: 886-2-2260-6878
 FAX: 886-2-2260-8030

品名 TITLE	5.0mm Terminal Block				頁數 Page	1/1
品號 PART NO.	△ 5TP508N-2RENXXXLX-01 △				繪圖 DRAWN	Eric 2018/12/10
圖號 DRAWING NO.	GN011-EA231	版本 REV.	D	核對 CHECKED	Josh 2018/12/10	
客戶品號 CUSTOMER P/N		比例 SCALE	None	承認 APPROVED	Jason 2018/12/10	
公差 TOLERANCE		單位 UNIT	mm	THIRD ANGLE PROJECTION		