

ELECTRICAL

Standard: UL IEC
Rated Voltage: 300V 450V
Rated Current: 15A 17.5A
Contact Resistance: 20mΩ
Withstanding Voltage: AC 2000V for one min
Insulation Resistance: 500MΩ
Wire range: 28-14AWG 1.5mm²

MECHANICAL

Temp. Range: -40°C ~ +105°C
Torque: 0.5Nm
Steip length: 7-8mm

MATERIAL

Housing: PA66, UL94V-0
Screws: M3 steel, Zn plated
Pin header: Copper alloy, Ni plated
Cage: Copper alloy, Ni plated

ORDER INFORMATION

5 T P 5 0 8 N - 2 R Z N X X E L X - 0 1

Series No.

Poles
(02-24P)

E:Green


A:Tray
B:Bag



AMTEK 糧德

2020.10.13

Released DCC



XX=08P-24P

04-07P

02P,03P

linear dimension(Tolerances Standard GB/T 14486-2008)



variable range	to 6	over 6 to 10	over 10 to 30	over 30 to 60	over 60 to 100	over 100 to 160	over 160 to 10	over 10 to 100	over 100 to 100	
tolerance	±0.20	±0.30	±0.50	±0.70	±1.00	±1.30	±1.60	0.10	0.30	0.60

Rev.1

ECN NO:200718 Revise the Tolerance

Alice

2020/09/23

REV.

ECN NO. OR DESCRIPTION

REVISED

DATE



糧德精密有限公司
Amtek Technology Co., Ltd.

TEL: 886-2-2260-6878
FAX: 886-2-2260-8030

品名 TITLE	5.08mm Terminal Block				頁數 Page	1/1
品號 PART NO.	5TP508N-2RZNXXELX-01				繪圖 DRAWN	Eric 2018/12/06
圖號 DRAWING NO.	GN011-EA202		版本 REV.	B	核對 CHECKED	Josh 2018/12/06
客戶品號 CUSTOMER P/N			比例 SCALE	None	承認 APPROVED	Jason 2018/12/06
公差 TOLERANCE			單位 UNIT	mm	THIRD ANGLE PROJECTION	