

ELECTRICAL

Standard: UL IEC
 Rated Voltage: 300V 250V
 Rated Current: 8A 10A
 Contact Resistance: 20mΩ
 Withstanding Voltage: AC 2000V for one min
 Insulation Resistance: 500MΩ

MECHANICAL

Temp. Range: -40°C ~ +105°C




MATERIAL

Housing: PA66, UL94V-0
 Screws: M2.0 Steel, Zn plated
 Clamp: Phosphor bronze, Ni plated
 Cage: Brass, Ni plated

ORDER INFORMATION

5 T P 5 0 8 N - 5 K 3 E X X E L X - 0 1

Series No. Poles (02-24P) E:Green A:Tray B:Bag



linear dimension(Tolerances Standard GB/T 14486-2008)							— □ ⊥			
variable range	to 6	over 6 to 10	over 10 to 30	over 30 to 60	over 60 to 100	over 100 to 160	to 10	over 10 to 100	over 100 to 160	
tolerance	±0.20	±0.30	±0.50	±0.70	±1.00	±1.30	±1.60	0.10	0.30	0.60

△Bx1	ECN NO:200718 Revise the Tolerance	Alice	2020/09/23
REV.	ECN NO. OR DESCRIPTION	REVISED	DATE

糧德精密有限公司
 Amtek Technology Co., Ltd.
 TEL: 886-2-2260-6878
 FAX: 886-2-2260-8030

品名 TITLE	3.81mm Terminal Block			頁數 Page	1/1
品號 PART NO.	5TP508N-5K3EXXELX-01			繪圖 DRAWN	Eric 2018/11/29
圖號 DRAWING NO.	GN011-EA137	版本 REV.	B	核對 CHECKED	Josh 2018/11/29
客戶品號 CUSTOMER P/N		比例 SCALE	None	承認 APPROVED	Jason 2018/11/29
公差 TOLERANCE		單位 UNIT	mm	THIRD ANGLE PROJECTION	