

ORDER INFORMATION

Electrical

Standard: UL IEC
Rated Voltage: 300V 450V
Rated Current: 15A 17.5A
Contact Resistance: 20mΩ
Insulation Resistance: 500MΩ / DC 500V
Withstanding Voltage: AC 2000V for one minute
Wire range: 28~14AWG 1.5mm²

Mechanical


Temp. Range: -40°C~+105°C
Torque(Max): 0.5Nm(4.5Lb.in)
Steip Length: 7-8mm

Dimensions



Pitch: 7.5mm
Poles: 2-24P

Material


Housing: Nylon66, UL94V-0
Screws: M3 Steel Zn plated
Clamp: Phosphor bronze, Ni plated
Cage: Brass, Ni plated



Released DCC



SECTION: A-A



Old Part No. : TB2EK-7.5-XXP-1X-00A-L

linear dimension (Tolerances Standard GB/T 14486-2008)



variable range	to 6	over 6 to 10	over 10 to 30	over 30 to 60	over 60 to 100	over 100 to 160	over 160 to 250	to 10	over 10 to 100	over 100 to 250
tolerance	±0.20	±0.30	±0.50	±0.70	±1.00	±1.30	±1.60	0.10	0.30	0.60

ECN NO.: 230714 Revise the PART NO

ECN NO.: 200718 Revise the Tolerance

Benson

2023/08/29

ECN NO. OR DESCRIPTION

REVISED

DATE



耀德精密有限公司
Amtek Technology Co., Ltd.

TEL: 886-2-2260-6878
FAX: 886-2-2260-8030

品名 TITLE	Terminal Block				頁數 Page	1/1
品號 PART NO.	5TP750N-2EKNXXXLX-01				繪圖 DRAWN	Mia 2016/08/18
圖號 DRAWING NO.	GN011-AL334	版本 REV.	C	核對 CHECKED	Boris 2016/08/18	
客戶品號 CUSTOMER P/N		比例 SCALE	None	承認 APPROVED	Boris 2016/08/18	
公差 TOLERANCE		單位 UNIT	mm	THIRD ANGLE PROJECTION		