

Electrical



Standard: UL IEC
Rated Voltage: 300V 400V
Rated Current: 15A 12A
Dielectric Voltage: AC 1600V for one minute
Temp. Range: -40°C ~ +105°C

Material

Housing: PA66, UL94V-0
Contact: Copper alloy, Tin plated
Screw: M3

ORDER INFORMATION

5	T	P	7	6	2	N	-	2	E	R	E	X	X	E	L	X	-	0	1
Series No.								No. of Poles (02~24P)				E:Green			B:Bag A:Tray				



SECTION A-A



linear dimension(Tolerances Standard GB/T 14486-2008)



variable range	to 6	over 6 to 10	over 10 to 30	over 30 to 60	over 60 to 100	over 100 to 160	over 160 to 250	to 10	over 10 to 100	over 100 to 250
tolerance	±0.20	±0.30	±0.50	±0.70	±1.00	±1.30	±1.60	0.10	0.30	0.60

REV.	ECN NO. OR DESCRIPTION	REVISED	DATE
	ECN NO:200718 Revise the Tolerance	Alice	2020/12/24


糧德精密有限公司
Amtek Technology Co., Ltd.
TEL: 886-2-2260-6878
FAX: 886-2-2260-8030

品名 TITLE	Terminal Block				頁數 Page	1/1
品號 PART NO.	5TP762N-2EREXXELX-01				繪圖 DRAWN	David 2020/03/20
圖號 DRAWING NO.	GN011-DV929	版本 REV.	B	核對 CHECKED	Josh 2020/03/20	
客戶品號 CUSTOMER P/N		比例 SCALE	None	承認 APPROVED	Josh 2020/03/20	
公差 TOLERANCE		單位 UNIT	mm	THIRD ANGLE PROJECTION		