

ELECTRICAL

Standard: UL IEC
 Rated Voltage: 300V 400V
 Rated Current: 30A 32A
 Contact Resistance: 20mΩ
 Withstanding Voltage: AC 1600V for one min
 Insulation Resistance: 500MΩ

MECHANICAL

Temp. Range: -40°C ~ +105°C

MATERIAL

Housing: PA66, UL94V-0
 Contactor: Copper alloy, Sn plated


ORDER INFORMATION

5 T P 7 6 2 R - 3 E C N X X E L X - 0 1




Series No.

Poles
(02-24P)

E:Green

A:Tray
B:Bag

Recommended PCB Layout



linear dimension(Tolerances Standard GB/T 14486-2008)



linear dimension(Tolerances Standard GB/T 14486-2008)								—		
variable range	to 6	over 6 to 10	over 10 to 30	over 30 to 60	over 60 to 100	over 100 to 160	over 160 to 10	to 10	over 10 to 100	over 100 to
tolerance	±0.20	±0.30	±0.50	±0.70	±1.00	±1.30	±1.60	0.10	0.30	0.60

REV.1

ECN NO:200718 Revise the Tolerance

Alice

2020/09/30

ECN NO. OR DESCRIPTION

REVISED

DATE



糧德精密有限公司
 Amtek Technology Co., Ltd.

TEL: 886-2-2260-6878
 FAX: 886-2-2260-8030

品名 TITLE	7.62mm Terminal Block				頁數 Page	1/1
品號 PART NO.	5TP762R-3ECNXXELX-01				繪圖 DRAWN	Eric 2018/12/21
圖號 DRAWING NO.	GN011-EA368		版本 REV.	B	核對 CHECKED	Josh 2018/12/21
客戶品號 CUSTOMER P/N			比例 SCALE	None	承認 APPROVED	Jason 2018/12/21
公差 TOLERANCE			單位 UNIT	mm	THIRD ANGLE PROJECTION	