

Standard:	UL	IEC
Rated Voltage:	300V	400V
Rated Current:	30A	32A
Contact Resistance:	20mΩ	
Withstanding Voltage:	AC 2000V	
Insulation Resistance:	500MΩ	

MECHANICAL

Temp. Range: -40°C ~ +105°C

MATERIAL

Housing: PA66, UL94V-0

Contactor: Copper alloy, Sn plated

ORDER INFORMATION





5 T P 7 6 2 S - 3 E C N X X E L X - 0 1

Series No.

Poles
(02-24P)

E:Green

A:Tray
B:Bag



linear dimension(Tolerances Standard GB/T 14486-2008)



variable range	to 6	over 6 to 10	over 10 to 30	over 30 to 60	over 60 to 100	over 100 to 160	over 160 to 250	to 10	over 10 to 100	over 100 to 250
tolerance	±0.20	±0.30	±0.50	±0.70	±1.00	±1.30	±1.60	0.10	0.30	0.60



ECN NO:200718 Revise the Tolerance

Alice

2020/09/30

ECN NO. OR DESCRIPTION

REVISÉD

DATE _____



糧德精密有限公司
Amtek Technology Co., Ltd.

TEL: 886-2-2260-6878
FAX: 886-2-2260-8030

品名 TITLE	7.62mm Terminal Block				頁數 Page	1/1
品號 PART NO.	5TP762S-3ECNXXELX-01			繪圖 DRAWN	Eric 2018/12/21	
圖號 DRAWING NO.	GN011-EA366	版本 REV.	B	核對 CHECKED	Josh 2018/12/21	
客戶品號 CUSTOMER P/N		比例 SCALE	None	承認 APPROVED	Jason 2018/12/21	
公差 TOLERANCE		單位 UNIT	mm	THIRD ANGLE PROJECTION		