

ELECTRICAL

Standard: UL IEC
Rated Voltage: 300V 320V
Rated Current: 10A 21A
Contact Resistance: 20mΩ
Withstanding Voltage: AC 2000V for one min
Insulation Resistance: 500MΩ
Wire range: 28-12AWG 2.5mm²

MECHANICAL

Temp. Range: -40°C ~ +105°C
Steip length: 5-6mm

MATERIAL

Housing: PA66, UL94V-0
Pin header: Copper alloy, Sn plated
Shrapnel: Stainless steel

ORDER INFORMATION

5 T R 5 0 8 L -

4 T 3

N X X

X L


X - 0 1

Series No.





No of Pins total
(06~72P)

O:Orange

A:Tray
B:Bag



Recommended PCB Layout
(PCB TOLERANCE ±0.05)



linear dimension(Tolerances Standard GB/T 14486-2008)



variable range	to 6	over 6 to 10	over 10 to 30	over 30 to 60	over 60 to 100	over 100 to 160	over 160 to	to 10	over 10 to 100	over 100 to
tolerance	±0.20	±0.30	±0.50	±0.70	±1.00	±1.30	±1.60	0.10	0.30	0.60

ECN NO:230714 Revise the PART NO.	Randy	2023/09/23
ECN NO:220814 Revise the PART NO.	Tim	2022/09/16
ECN NO:201126 Revise the PART NO.	Alice	2020/12/14
REV.	REVISED	DATE



耀德精密有限公司
Amtek Technology Co., Ltd.
TEL: 886-2-2260-6878
FAX: 886-2-2260-8030

品名 TITLE	5.08mm Terminal Block				頁數 Page	1/1
品號 PART NO.	△ 5TR508L-4T3NXXXXLX-01 △				繪圖 DRAWN	Eric 2018/12/26
圖號 DRAWING NO.	GN011-EA393		版本 REV.	E	核對 CHECKED	Josh 2018/12/26
客戶品號 CUSTOMER P/N			比例 SCALE	None	承認 APPROVED	Jason 2018/12/26
公差 TOLERANCE			單位 UNIT	mm	THIRD ANGLE PROJECTION	