

ELECTRICAL

Standard: UL IEC
Rated Voltage: 300V 160V
Rated Current: 10A 24A
Contact Resistance: 20mΩ
Withstanding Voltage: AC 2000V for one min
Insulation Resistance: 500MΩ
Wire range: 22-14AWG 2.5mm²

MECHANICAL

Temp. Range: -40°C ~ +105°C
Torque: 0.4Nm
Steip length: 6-7mm

MATERIAL

Housing: PA66, UL94V-0
Contactor: Copper alloy
Screw: M3

ORDER INFORMATION

5 T S 5 0 0 S -

1 2 2

N

X X

X

L


X - 0 1

Series No.



Poles
(02-24P)

E:Green
B:Black

A:Tray
B:Bag



Recommended PCB Layout



linear dimension(Tolerances Standard GB/T 14486-2008)



variable range	to 6	over 6 to 10	over 10 to 30	over 30 to 60	over 60 to 100	over 100 to 160	over 160 to	to 10	over 10 to 100	over 100 to
tolerance	±0.20	±0.30	±0.50	±0.70	±1.00	±1.30	±1.60	0.10	0.30	0.60

△x1	Add the LOGO	David	2023/02/13
△x2	Add the Black Options	Alice	2022/03/16
△x1	ECN NO:200718 Revise the Tolerance	Alice	2020/12/07
REV.	ECN NO. OR DESCRIPTION	REVISED	DATE



糧德精密有限公司
Amtek Technology Co., Ltd.
TEL: 886-2-2260-6878
FAX: 886-2-2260-8030

品名 TITLE	5.0mm Terminal Block				頁數 Page	1/1
品號 PART NO.	△ 5TS500S-122NXXXLX-01				繪圖 DRAWN	Eric 2018/12/13
圖號 DRAWING NO.	GN011-EA273	版本 REV.	D	核對 CHECKED	Josh 2018/12/13	
客戶品號 CUSTOMER P/N		比例 SCALE	None	承認 APPROVED	Jason 2018/12/13	
公差 TOLERANCE		單位 UNIT	mm	THIRD ANGLE PROJECTION		