

ELECTRICAL

Standard: UL IEC
 Rated Voltage: 300V 300V
 Rated Current: 16A 10A

Contact Resistance: 20mΩ

Withstanding Voltage: AC1600V for one min

Insulation Resistance: 500MΩ

Wire range: 22-12AWG 2.5mm²

MECHANICAL

Temp. Range: -40°C ~ +105°C

Strip length: 6-7mm

MATERIAL

Housing: PA66, UL94V-0

Screws: M2.5 Steel Zn plated

Contact: Copper alloy

ORDER INFORMATION

5 T S 7 6 2 S -

1 2 E N X X


E L X - 0 1

Series No.


Poles
(02-16P)

E:Green


A:Tray
B:Bag



P.C.B. LAYOUT



SECTION:A-A



linear dimension(Tolerances Standard GB/T 14486-2008)



variable range	to 6	over 6 to 10	over 10 to 30	over 30 to 60	over 60 to 100	over 100 to 160	over 160 to	to 10	over 10 to 100	over 100 to
tolerance	±0.20	±0.30	±0.50	±0.70	±1.00	±1.30	±1.60	0.10	0.30	0.60

REV.	ECN NO. OR DESCRIPTION	REVISED	DATE
	ECN NO:200718 Revise the Tolerance	Alice	2020/12/10



耀德精密有限公司
Amtek Technology Co., Ltd.

TEL: 886-2-2260-6878
FAX: 886-2-2260-8030

品名 TITLE	7.62mm Terminal Block				頁數 Page	1/1
品號 PART NO.	5TS762S-12ENXXELX-01				繪圖 DRAWN	Eric 2018/11/21
圖號 DRAWING NO.	GN011-EA051		版本 REV.	B	核對 CHECKED	Josh 2018/11/21
客戶品號 CUSTOMER P/N			比例 SCALE	None	承認 APPROVED	Jason 2018/11/21
公差 TOLERANCE			單位 UNIT	mm	THIRD ANGLE PROJECTION	