Specification:
Contact Resistance: 30m Ohm Max.
Insulation Resistance: 1000M Ohm Min. At 500VDC.
Rated Voltage And Current: 1.5A At 250VAC Minimum.
Dielectric Withstanding Voltage: 750V AC (rms) for 1 Minute
Durability (Life Test): 1500 Cycles
Insertion Force: 35 Newtone Maximum.
Extraction Force: 10 Newtone Minimum.

ORDER INFORMATION

5 U S 2 A 1 6 M M - 1 0 4 S 0 X U A D 1

- M:Male
- 1:1 Port
- No. of contacts
- S0: Selective
- B:Black / W:White
- RoHS
- A:Tray W/O Cap

Amtek
2017.08.23
文管中心



COMPONENT SIDE
(PCB LAYOUT)



Old Part No. :USB-001MRS-AXS-U

NO.	NAME	MATERIAL	FINISH	Q'TY	REMARK
1	HOUSING	NYLON PA9T G.F.	BLACK/WHITE	1	
2	TERMINAL	BRASS E-H T:0.25	GOLD/TIN PLATED	4	Gold:1~3u"; NI:40~60u"; TIN:120u" (100% pure Tin of lead free plating)
3	SHELL	SPCC T:0.3	NICKEL PLATED	1	Ni:80~120u"

REV.	ECN NO. OR DESCRIPTION	REVISED	DATE
B	Revise the drawing	B	2016/06/20 Roy

AMTEK
糧德精密有限公司
Amtek Technology Co., Ltd.
TEL: 886-2-2260-6878
FAX: 886-2-2260-8030

品名 TITLE	USB A PLUG PCB REVERSE FLAT SMT			頁數 Page	1/1
品號 PART NO.	5US2A16MM-104S0XUAD1			繪圖 DRAWN	Mia 2015/10/07
圖號 DRAWING NO.		版本 REV.	B	核對 CHECKED	John 2015/10/07
客戶品號 CUSTOMER P/N		比例 SCALE	None	承認 APPROVED	John 2015/10/07
公差 TOLERANCE	.X ± 0.25 .XX ± 0.13	單位 UNIT	mm	THIRD ANGLE PROJECTION	