ELECTRICAL

Standard: UL IEC
Rated Voltage: 300V 250V
Rated Current: 15A 16A
Contact Resistance:20mΩ
Insulation Resistance: 500MΩ / DC 500V
Wire Rang:28~12AWG 2.5mm²
Withstanding Voltage: AC 2000V for one minute

MECHANICAL

Steip Length:8-9mm
Temp.Range:-40°C~+105°C

Dimensions

Pitch:7.62mm
Poles:2-24P

MATERIAL

Housing: PA66, UL94V-0
Wire guard:Stainless Steel
Pin header:Copper alloy ,Sn plated

ORDER INFORMATION

5 T M 7 6 2 N - J 0 4 N X X O L X - 0 1

- J04: Series No.
- NXX: No of Pins total (02-24)
- O: O:Orange
- X: A:Tray / B:Bag

certified Pb RoHS Compliant



AMTEK糧德
2020.11.30
Released DCC









B

linear dimension(Tolerances Standard GB/T 14486-2008)								—	▱	⊥
variable range	to 6	over 6 to 10	over 10 to 30	over 30 to 60	over 60 to 100	over 100 to 160	over 160 to	to 10	over 10 to 100	over 100 to
tolerance	±0.20	±0.30	±0.50	±0.70	±1.00	±1.30	±1.60	0.10	0.30	0.60

REV.	ECN NO. OR DESCRIPTION	REVISED	DATE
B x1	ECN NO:200718 Revise the Tolerance	Alice	2020/11/04

糧德精密有限公司
Amtek Technology Co., Ltd.
TEL: 886-2-2260-6878
FAX: 886-2-2260-8030

品名 TITLE	Terminal Block			頁數 Page	1/1
品號 PART NO.	5TM762N-J04NXXOLX-01			繪圖 DRAWN	Benson 2020/02/03
圖號 DRAWING NO.	GN011-BS798	版本 REV.	B	核對 CHECKED	Josh 2020/02/03
客戶品號 CUSTOMER P/N		比例 SCALE	None	承認 APPROVED	Josh 2020/02/03
公差 TOLERANCE		單位 UNIT	mm	THIRD ANGLE PROJECTION	