

SPECIFICATIONS

CURRENT RATE:3 AMP
INSULATION RESISTANCE:5000M Ω MIN.
DIELECTRIC VOLTAGE:500V AC FOR ONE MINUTE
OPERATION TEMPERATURE:-40°C TO +105°C

MATERIAL

INSULATOR:PBT, UL94V-0
TERMINAL:COPPER ALLOY

FINISH

GOLD PLATED ON CONTACT AREA, NICKLE UNDERPLATED OVERALL

ORDER INFORMATION

5J P 3 X A - 2 1 X X X X L - 0 1

©:Standard Recommend

E

P = PHOSPHOR

A:CLOSE 3.0mm

C

G0:GOLD FLASH

GA:5U"

B

B:BLACK INSULATOR
U:BLUE INSULATOR
G:GRAY INSULATOR
R:RED INSULATOR
E:GREEN INSULATOR
W:WHITE INSULATOR
Y:YELLOW INSULATOR

B

B:BAG

L

L:RoHS +PBT

Technical drawing of a mini jumper component. The drawing includes three views: a top view, a side view, and a detailed contact area view. Dimensions are provided in millimeters (mm) with tolerances.

- Top View Dimensions:
 - Overall width: 2.5 ± 0.1
 - Inner width: 2.3 ± 0.05
 - Overall height: 1.49 ± 0.1
 - Inner height: 2
 - Bottom width: 1.27 ± 0.05
 - Bottom height: 2 ± 0.05
- Side View Dimensions:
 - Overall height: 0.5
 - Inner height: 2.5
 - Bottom width: 0.75 ± 0.05
- Contact Area View Dimensions:
 - Overall width: 3 ± 0.2
 - Inner width: 2.5 ± 0.1
 - Inner height: 2.3 ± 0.05
 - Bottom width: 1.27 ± 0.05
 - Bottom height: 2 ± 0.05

				 糧德精密有限公司 Amtek Technology Co., Ltd. TEL: 886-2-2260-6878 FAX: 886-2-2260-8030	品名 TITLE	MINI JUMPER 1.27mm				頁數 Page	1/1
					品號 PART NO.	5JP3XA-21XXXXL-01(CN047)		繪圖 DRAWN	Roy 2016/03/25		
					圖號 DRAWING NO.	GN047-MC671	版本 REV.	E	核對 CHECKED	Owen 2016/03/25	
					客戶品號 CUSTOMER P/N		比例 SCALE	None	承認 APPROVED	John 2016/03/25	
					公差 TOLERANCE	.X ± 0.25 .XX ± 0.13	單位 UNIT	mm	THIRD ANGLE PROJECTION		
E	REC N2503000064		Alice	2025/03/18							
D x2	ECN NO.230113: Revise the Specification & Drawing		Rex	2023/03/29							
C x2	Add GA:5u"		David	2019/05/23							
REV.	ECN NO. OR DESCRIPTION		REVISED	DATE							