

MATERIAL

Insulator: Nylon9T, UL94V-0, Black
Contact Pin: Phosphor Bronze

ORDER INFORMATION


5 P S 3 M S B 2 1 - 2 X X X X X X X U - 0 0

2: Dual Row	No. of Pin Per Row(04~50)	③ G0: Gold Flash	S0: Selective	N: W/O Peg P: With Peg	T: Tube W/O Cap C: Tube With Cap R: T/R With Cap	RoHS
		GA: 5u"	SA: 5u"			
		GB: 10u"	SB: 10u"	N: W/O Bump	N: N Type	
		GC: 20u"	SC: 20u"			
		GD: 30u"	SD: 30u"			
		T0: Tin Plated				
		TE: Tin 200u"				

AMTEK 耀德

2024.01.05

Released DCC



Old Part No. : PS3M21-2XX-U

	ECN 231005.: Revise the drawing	Alice	2023/10/23
 x2	ECN NO.230523: Revise the drawing	Alice	2023/06/19
 x7	ECN NO.210532: Revise the drawing	David	2021/06/15
REV.	ECN NO. OR DESCRIPTION	REVISED	DATE



耀德精密有限公司
Amtek Technology Co., Ltd.
TEL: 886-2-2260-6878
FAX: 886-2-2260-8030

品名 TITLE	FEMALE HEADER 1.27mm				頁數 Page	1/1
品號 PART NO.	5PS3MSB21-2XXXXXXXU-00				繪圖 DRAWN	Roy 2017/02/10
圖號 DRAWING NO.	GN005-RL441	版本 REV.	E	核對 CHECKED	Josh 2019/02/12	
客戶品號 CUSTOMER P/N		比例 SCALE	None	承認 APPROVED	Josh 2019/02/12	
公差 TOLERANCE	.X ± 0.30 .XX ± 0.20	X° ± 3°	單位 UNIT	mm	THIRD ANGLE PROJECTION	