


SPECIFICATIONS

Current Rating: 1.5 AMP
Voltage Rating: 125 Vac Rms.
Insulation Resistance: 1000MΩ Min@500Vdc
Contact Resistance: 40mΩ Max.
Dielectric Strength: 1000Vac Rms 60Hz,1Min
Durrability:750 Cycles
Operation Temperature: -20°C~75°C
Storage Temperature:-40°C~85°C

MATERIALS

Housing:PBT,UL94V-0
Contacts:Phosphor bronze


ORDER INFORMATION






AMTEK 耀德

2023.07.17

Released DCC



Recommended PCB Layout
(PCB TOLERANCE ±0.05)



 耀德精密有限公司 Amtek Technology Co., Ltd. TEL: 886-2-2260-6878 FAX: 886-2-2260-8030	品名 TITLE	MODULAR JACK SIDE ENTRY				頁數 Page	1/1
	品號 PART NO.	5RJ1DR00N0X-AAXX00X-504-Y1				繪圖 DRAWN	Gaby 2023/07/03
	圖號 DRAWING NO.	GN225-GY003	版本 REV.	A	核對 CHECKED	Josh 2023/06/19	
	客戶品號 CUSTOMER P/N		比例 SCALE	None	承認 APPROVED	Josh 2023/06/19	
	公差 TOLERANCE	.X ± 0.38 .XX ± 0.25	.X°±3°	單位 UNIT	mm	THIRD ANGLE PROJECTION	

REV.	ECN NO. OR DESCRIPTION	REVISED	DATE