

ORDER INFORMATION

SPECIFICATION





CONTACT RESISTANCE: 30mΩ MAX.
INSULATOR RESISTANCE: 100 MΩ MIN.
DIELECTNIC VOLTAGE: 500V AC ONE SEC LEVEL
OPERATING TEMPERATURE :-25°C ~ +85°C

MATERIAL

HOUSING: PPA,UL94V-0
TERMINAL(+): PHOSPHOR BRONZE,T:0.2mm
TERMINAL(-): PHOSPHOR BRONZE,T:0.2mm

5 S B D 2 0 3 2 M 2 - X X X U X - J 0 1

G0:GOLD FLASH
N:BROWN
U:RoSH
A:TRAY W/O CAP



RECOMMENDED PCB LAYOUT
(PCB TOLERANCE ±0.05)

 耀德精密有限公司 Amtek Technology Co., Ltd. TEL: 886-2-2260-6878 FAX: 886-2-2260-8030	品名 TITLE	BATTERY HOLDER 2032 SMT V/T TYPE				頁數 Page	1/1
	品號 PART NO.	5SBD2032M2-XXXUX-J01				繪圖 DRAWN	Gaby 2024/03/21
	圖號 DRAWING NO.	GN224-GY573	版本 REV.	A	核對 CHECKED	Josh 2024/03/21	
	客戶品號 CUSTOMER P/N		比例 SCALE	None	承認 APPROVED	Josh 2024/03/21	
	公差 TOLERANCE	.X ± 0.25 .XX ± 0.20	.XXX±0.1 X°±1°	單位 UNIT	mm	THIRD ANGLE PROJECTION	

REV.	Easy Flow 202403200005	Gaby	2024/03/21
	ECN NO. OR DESCRIPTION	REVISED	DATE