

ELECTRICAL

STANDARD: UL IEC
RATED VOLTAGE: 300V 450V
RATED CURRENT: 15A 32A
CONTACT RESISTANCE: 20mΩ
WITHSTANDING VOLTAGE: AC 2000V FOR ONE MIN
INSULATION RESISTANCE: 500MΩ
WIRE RANGE: 22-10AWG 0.5-4.0mm²

MECHANICAL




TEMP. RANGE: -40°C ~ +105°C
TORQUE: 0.4Nm

MATERIAL

HOUSING: PA66, UL94V-0
SCREWS: M2.5 STEEL, Zn PLATED
PRESSURE LINE COLUMN: SPCC Zn PLATED

ORDER INFORMATION

5	T	F	8	2	0	N	-	8	H	S	N	X	X	X	L	X	-	0	1
Series No.								NO OF POLES TOTAL (02-12P)				W:NATURAL				B:BAG-2PIN~4PIN X:BOX-5PIN~12PIN			



SECTION A-A



linear dimension(Tolerances Standard GB/T 14486-2008)								—	□	⊥
variable range	to 6	over 6 to 10	over 10 to 30	over 30 to 60	over 60 to 100	over 100 to 160	over 160 to	to 10	over 10 to 100	over 100 to
tolerance	±0.20	±0.30	±0.50	±0.70	±1.00	±1.30	±1.60	0.10	0.30	0.60

△	ECN 202502009	Willy	2025/03/07
△	ECN NO:230714 Revise the PART NO.	Alice	2023/09/23
△x2	ECN NO:201210 Revise the PART NO.	Alice	2020/12/18
REV.	ECN NO. OR DESCRIPTION	REVISED	DATE

糧德精密有限公司
Amtek Technology Co., Ltd.
TEL: 886-2-2260-6878
FAX: 886-2-2260-8030

品名 TITLE	TERMINAL BLOCK FEED THROUGH 8.2mm				頁數 Page	1/1
品號 PART NO.	5TF820N-8HSNXXLLX-01				繪圖 DRAWN	Eric 2018/12/27
圖號 DRAWING NO.	GN011-EA410	版本 REV.	F	核對 CHECKED	Josh 2018/12/27	
客戶品號 CUSTOMER P/N		比例 SCALE	None	承認 APPROVED	Jason 2018/12/27	
公差 TOLERANCE		單位 UNIT	mm	第三 ANGLE PROJECTION		