






Specification:

1. Rated voltage and current: 1A Max.
2. Dielectric withstanding voltage: 30V(ac) for 1 minute.
3. Contact resistance: Before life test 30m ohm Max.
After life test 50m ohm max
4. Insulation resistance: 1000M ohm Min at DC 500V.
5. Insertion force: 35 Newtons Max.
6. Extraction force: 10 Newtons Min.
7. Solderability: Terminal shall be immersed in flux before text, Then dip in molten solder for 5 ± 0.5 sec. At $245 \pm 5^\circ\text{C}$
8. Temperature range: $-55^\circ\text{C} \sim +85^\circ\text{C}$

ORDER INFORMATION



3	Shell	1	Brass	T=0.30mm	80~120u"Nickel Plated
2	Contact	4	Brass	T=0.25mm	Contact area:0.8~1.2u" Gold Plated over 40u"Nickel min. Solder area:80~120u" Tin Plated over 40u" Nickel min.
1	Housing	1	P.B.T	UL 94-V0	White
No.	Name	Q'ty	Material	Remarks & Thickness	Finish

Old Part No.:USB-FS-AW-L

REV.	ECN NO. OR DESCRIPTION	REVISED	DATE

 糧德精密有限公司 Amtek Technology Co., Ltd. TEL: 886-2-2260-6878 FAX: 886-2-2260-8030	品名 TITLE	USB A TYPE FEMALE SOLDER				頁數 Page	1/1
	品號 PART NO.	5US2A15SF-104S0WLBC1				繪圖 DRAWN	Jeff 2016/11/17
	圖號 DRAWING NO.	GW062-JF019				核對 CHECKED	Johnny 2016/11/17
	客戶品號 CUSTOMER P/N					承認 APPROVED	Aaron 2016/11/17
	公差 TOLERANCE	.X ± 0.30 .XX ± 0.20				單位 UNIT	mm
						THIRD ANGLE PROJECTION	