




SPECIFICATIONS 
DIELECTRIC STRENGTH: 250VAC 50Hz 1 MIN
RATING:DC 6V 0.3A MAX
CONTACT RESISTANCE:200mΩ MAX.
INSULATION RESISTANCE:100MΩ MIN
OPERATING LIFE:10,000 CYCLES
OPERATING FORCE:160gf±100gf
TRAVEL:2.0±0.2mm

MATERIALS
BASE:LCP,BLACK
TERMINAL:BRASS,SILVER PLATED
CONTACT:BERYLLIUM COPPER,SILVER PLATED
COVER:STAINLESS STEEL 
ACTUATOR:NYLON 46,BLACK





ORDER INFORMATION



CIRCUIT DIAGRAM



RECOMMENDED PCB LAYOUT
(PCB TOLERANCE ±0.05)



	REC2511000011	Oliver	2025/11/04
	REC2507000047	Willy	2025/07/09
	REC2507000006	Willy	2025/07/03
REV.	ECN NO. OR DESCRIPTION	REVISED	DATE

 糧德精密有限公司 Amtek Technology Co., Ltd. TEL: 886-2-2260-6878 FAX: 886-2-2260-8030	品名 TITLE	SLIDE SWITCH DIP V/T TYPE				頁數 Page	1/1
	品號 PART NO.	6SSDS01-XXXXXXXXXF01				繪圖 DRAWN	JOHN 2025/06/10
	圖號 DRAWING NO.	GN219-JH354	版本 REV.	D	核對 CHECKED	JOSH 2025/06/10	
	客戶品號 CUSTOMER P/N		比例 SCALE	None	承認 APPROVED	JOSH 2025/06/10	
	公差 TOLERANCE	5<L≤10 ±0.3 L≤5 ±0.2	單位 UNIT	mm	THIRD ANGLE PROJECTION		