







SPECIFICATIONS 
DIELECTRIC STRENGTH: AC110V 50Hz/1MIN
RATING:DC12V,50mA MAX
CONTACT RESISTANCE:70mΩ MAX
INSULATION RESISTANCE:100MΩ MIN
OPERATING LIFE:10,000 CYCLES
OPERATING FORCE:200gf±50gf
TRAVEL:1.5±0.1mm
OPERATING TEMPERATURE:-10°C~+60°C

MATERIALS 
BASE:LCP, BLACK
TERMINAL: BRASS, SILVER PLATED
CONTACT: BERYLLIUM COPPER, SILVER PLATED
COVER: STAINLESS STEEL
ACTUATOR: NYLON46, BLACK

ORDER INFORMATION



RECOMMENDED PCB LAYOUT
(PCB TOLERANCE ±0.05)



	REC�2511000009	Oliver	2025/11/04
	REC�2507000113	Willy	2025/07/25
	REC�2507000052	Willy	2025/07/09
REV.	ECN NO. OR DESCRIPTION	REVISED	DATE


糧德精密有限公司
Amtek Technology Co., Ltd.
TEL: 886-2-2260-6878
FAX: 886-2-2260-8030

品名 TITLE	SLIDE SWITCH SMT V/T TYPE				頁數 Page	1/1
品號 PART NO.	6SSMS04-XXXXXXXXXF01			繪圖 DRAWN	JOHN 2025/06/10	
圖號 DRAWING NO.	GN219-JH364	版本 REV.	F	核對 CHECKED	JOSH 2025/06/10	
客戶品號 CUSTOMER P/N		比例 SCALE	None	承認 APPROVED	JOSH 2025/06/10	
公差 TOLERANCE	.X ± 0.2 .XX ± 0.1	單位 UNIT	mm	THIRD ANGLE PROJECTION		